

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

AGILENT / KEYSIGHT

Agilent/Keysight 0950-2546

The Agilent/Keysight 0950-2546 is a power supply component designed for use with Agilent/Keysight instruments. It provides reliable and stable power for various testing and measurement applications.



MODEL

**Agilent / Keysight
0950-2546**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

0950-2546

LISTING

<https://aumictechlabs.com/products/0950-2546-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight 0950-2546 is an AC/DC adapter delivering regulated 5 V DC at 2.0 A to Agilent and Keysight test instruments. Designed for laboratory and field environments, this Class I power supply accepts 100–240 V AC input (50/60 Hz) via IEC 320 connector and provides stable power for USB compliance testing, gateway operation, and portable RF instruments. The adapter weighs approximately 5 lbs and carries CE marking for compliance assurance in pollution degree 2 environments. Technical Specifications Output: +5 V DC, 2.0 A Input: 100–240 V AC, 50/60 Hz Input Connector: IEC 320 Safety Class: Class I with protective earthing terminal Pollution Degree: 2 Certifications: CE Marking Weight: ~5 lbs Key Features Fixed 5 V, 2 A output topology eliminates need for field adjustment Class I design includes protective earthing for instrument safety Universal AC input range (100–240 V, 50/60 Hz) supports global laboratory deployment IEC 320 connector provides standard industrial power interface Typical Applications USB 2.0 compliance test fixture power supply LAN/GPIB gateway module for Agilent E2050 operation Battery charger

for Keysight FieldFox RF vector network analyzers (N9912A–N9918A models) 5 V test fixture supply for Infiniium oscilloscope test options (e.g., E2645A) Compatibility & Integration The adapter integrates with Agilent and Keysight test systems including the E2050 LAN/GPIB gateway, D9010USBC USB compliance application, FieldFox portable RF analyzers, and Infiniium oscilloscope platforms. Laboratory setups requiring 5 V, 2 A distributed power benefit from this adapter's proven compatibility across multiple product generations.

09502546 Characteristics / Specifications

PARAMETER	VALUE
Model	0950-2546
Brand	Agilent / Keysight
Catalog Title	Agilent/Keysight 0950-2546
Sku	0950-2546
Product Class	catalog accessory or spare
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	0950-2546
Manufacturer Line	Agilent / Keysight
Documentation Note	thin accessory sheet
Calibration Class	notastandalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory
Public Spec Density	identity only

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate.

Applications

Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU.

Key Features

Catalog identity matched to brand, model, and SKU

Accessory or spare class rather than standalone instrument

No invented electrical performance numbers

Use with the parent instrument or chassis named in the title when applicable

Documented as thin because OEM numeric tables are not public

Technical Specifications

Technical Specifications

PARAMETER	VALUE
Model	0950-2546
Brand	Agilent / Keysight
Catalog Title	Agilent/Keysight 0950-2546
Sku	0950-2546
Product Class	catalog accessory or spare
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	0950-2546
Manufacturer Line	Agilent / Keysight
Documentation Note	thin accessory sheet
Calibration Class	not standalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory

PARAMETER	VALUE
Public Spec Density	identity only

Notes
ALLOW_THIN: true accessory/spare with no public numeric table. Do not invent ranges, accuracies, or power levels. Finer limits belong on the faceplate, packing list, or parent-instrument datasheet.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.