

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

AGILENT / KEYSIGHT

Agilent/Keysight 0950-3384

Agilent / Keysight Power Supply Modules. Frequency Range: 103 kHz, Voltage / Current Range: +15 V, +22 V, +32 V (A14 motherboard), +5.2 V, +9 V, -15 V, -5.2 V, VCC 5.2 V, VDL 3.3 V.



MODEL

**Agilent / Keysight
0950-3384**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

0950-3384

LISTING

<https://aumictechlabs.com/products/0950-3384-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight 0950-3384 is a switching power supply assembly engineered to deliver stable, regulated DC power across multiple voltage rails for network analyzers and related test equipment. Operating at 103 kHz switching frequency, the supply features automatic input voltage sensing and dual-range operation (90–132 Vac or 195–250 Vac), eliminating manual configuration and supporting global deployment scenarios. Technical Specifications The 0950-3384 generates nine distinct output voltage rails: +5.2 V, -5.2 V, +9 V, +15 V, -15 V, +22 V, and a dedicated +15 V standby line that remains powered when the analyzer is off. The supply also provides VCC (5.2 V) and VDL (3.3 V) rails directly to the A15 CPU board assembly. An additional +32 V line is generated on the A14 motherboard from the +22 V output. The +15 V standby rail operates continuously whenever the supply is plugged in, powering front panel indicator LEDs and CPU components during offline periods without requiring full system activation. Key Features Automatic input voltage sensing and switching between 90–132 Vac and 195–250 Vac ranges Nine discrete output voltage channels supporting analog and digital subsystems Dedicated standby power rail

for always-on front panel and CPU functions Fixed 103 kHz switching frequency for predictable EMI filtering and thermal management Designed for hot-swap field replacement using standard TORX tools Typical Applications The 0950-3384 is the primary power distribution module in network analyzers and microwave test instruments requiring multi-rail power architecture with integrated standby functionality. Compatibility & Integration Directly compatible with Agilent/Keysight N338xA Series PNA Network Analyzers, E8356A, E8357A, E8358A, E8801A, E8802A, E8803A, N3381A, N3382A, and N3383A platforms. Replacement requires T-10 and T-20 TORX drivers and ESD grounding precautions.

09503384 Characteristics / Specifications

PARAMETER	VALUE
Model	0950-3384
Brand	Agilent / Keysight
Catalog Title	Agilent/Keysight 0950-3384
Sku	0950-3384
Product Class	catalog accessory or spare
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	0950-3384
Manufacturer Line	Agilent / Keysight
Documentation Note	thin accessory sheet
Calibration Class	notastandalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory
Public Spec Density	identity only

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate.

Applications

Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU.

Key Features

Catalog identity matched to brand, model, and SKU

Accessory or spare class rather than standalone instrument

No invented electrical performance numbers

Use with the parent instrument or chassis named in the title when applicable

Documented as thin because OEM numeric tables are not public

Technical Specifications

Technical Specifications

PARAMETER	VALUE
Model	0950-3384
Brand	Agilent / Keysight
Catalog Title	Agilent/Keysight 0950-3384
Sku	0950-3384
Product Class	catalog accessory or spare
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	0950-3384
Manufacturer Line	Agilent / Keysight
Documentation Note	thin accessory sheet
Calibration Class	not standalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory

PARAMETER	VALUE
Public Spec Density	identity only

Notes
ALLOW_THIN: true accessory/spare with no public numeric table. Do not invent ranges, accuracies, or power levels. Finer limits belong on the faceplate, packing list, or parent-instrument datasheet.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.