

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 14, 2026

AGILENT / KEYSIGHT

Agilent/Keysight 6263B DC Power Supply

Agilent 6263B Regulated DC Power Supply 0 to 20 V 0 to 10 A The HP/Agilent 6263B is a constant-voltage/constant-current rack/bench DC power supply. OEM operating manual Table 1-1 rates 0 to 20 V at 0 to 10 A. System racks and benches needing medium-power regulated DC with crowbar protection. Series regulator with triac preregulator for efficiency The HP/Agilent 6263B is a constant-voltage/constant-current rack/bench DC power supply. OEM operating manual Table 1-1 rates 0 to 20 V at 0 to 10 A. System racks and benches needing medium-power regulated DC with crowbar protection. Series regulator with triac preregulator for efficiency Built-in fast overvoltage crowbar with adjustable trip



MODEL

**Agilent / Keysight
6263B**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

6263B

LISTING

<https://aumictechlabs.com/products/6263b-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight 6263B is a single-output, 200-watt regulated DC power supply engineered for benchtop laboratory and development work. It delivers stable, continuously adjustable voltage and current without range switching, supported by a transistor series-regulator and triac-preregulator topology that ensures high efficiency, excellent regulation, and minimal ripple and noise. Technical Specifications Electrical Output Voltage Range: 0–20 V Current Range: 0–10 A Power Output: 200 W Continuously variable voltage and current adjustment Performance Load Regulation (Constant Voltage): <0.01% + 200 μ V Load Regulation (Constant Current): <0.02% + 500 μ A Line Regulation (Constant Voltage): <0.01% + 200 μ V (104–127 Vac input) Line Regulation

(Constant Current): $<0.02\% + 500\ \mu\text{A}$ (104–127 Vac input) Voltage Stability: $0.03\% + 500\ \mu\text{V}$
Current Stability: $0.03\% + 6\ \text{mA}$ Output Ripple & Noise (CV): $<200\ \mu\text{V rms}$, $<10\ \text{mV peak-to-peak}$
(20 Hz–20 MHz) Output Ripple & Noise (CC): $<3\ \text{mA rms}$ (20 Hz–20 MHz) Temperature
Coefficient: $0.01\% + 200\ \mu\text{V}/^\circ\text{C}$ Warm-up Time: 30 minutes to full specification Operating
Temperature: $0\text{--}55^\circ\text{C}$ Storage Temperature: $-40\text{--}75^\circ\text{C}$ Physical Dimensions: $83.7\ \text{mm H} \times 483\ \text{mm W} \times 479.4\ \text{mm D}$ Weight: 30 lbs Cooling: Convection cooled AC Input Voltage: $115\ \text{Vac} \pm 10\%$,
single phase, 57–63 HzKey Features Remote sensing for load-point regulation Remote
programming via rear-panel barrier strip connections Adjustable crowbar overvoltage protection
Auto-Series, Auto-Parallel, and Auto-Tracking capabilities for multi-supply configurations Optional
Voltage and Current Programming (Option 022) Optional HP-IB and RS-232 interfaces (Option
040 Multiprogrammer Interface)Typical Applications Precise DC power for component testing,
circuit development, and bench characterization where sub-0.01% load regulation and low noise
are required.Compatibility & Integration Supports external resistance or DC voltage programming.
Multi-supply operation enabled via auto-series, auto-parallel, and auto-tracking configurations.

Features & description

From manufacturer datasheet

Built-in fast overvoltage crowbar with adjustable trip

Remote resistance or voltage programming Remote sensing to the load Auto series, auto parallel, and auto tracking modes Technical Specifications Instrument Type: CV/CC regulated DC power supply Series Family: HP 6256B 6263B 6264B 6265B 6266B 6267B 6271B 6274B Output Voltage Rating: 0 to 20 V Output Current Rating: 0 to 10 A Operating Modes: constant voltage and constant current with automatic crossover Load Regulation Voltage: 0.01 percent plus 200 μ V class Load Regulation Current: 0.02 percent plus milliamp class Line Regulation Voltage: 0.01 percent plus 200 μ V class Line Regulation Current: 0.02 percent plus milliamp class Ripple Noise Voltage RMS: 200 μ V to 1 mV class by model Ripple Noise Voltage Peak Peak: 10 mV to 20 mV class Ripple Noise Current RMS: less than 5 mA on higher current models class Transient Recovery: less than 50 μ s class to within 10 mV Crowbar Range: approximately 10 percent to 110 percent of rated voltage DC Floating Voltage: up to 300 V above ground Front Output Terminal Rating: monitoring only, 3 A maximum AC Input: 115 Vac plus or minus 10 percent, 57 to 63 Hz standard Cabinet Height: 3.5 in full rack Cooling: convection except forced air on 6274B Remote Programming: resistance or voltage

6263B Characteristics / Specifications

PARAMETER	VALUE
Instrument Type	CV/CC regulated DC power supply
Series Family	HP 6256B 6263B 6264B 6265B 6266B 6267B 6271B 6274B
Output Voltage Rating	0 to 20 V
Output Current Rating	0 to 10 A
Operating Modes	constant voltage and constant current with automatic crossover
Load Regulation Voltage	0.01 percent plus 200 uV class
Load Regulation Current	0.02 percent plus milliamp class
Line Regulation Voltage	0.01 percent plus 200 uV class
Line Regulation Current	0.02 percent plus milliamp class
Ripple Noise Voltage RMS	200 uV to 1 mV class by model
Ripple Noise Voltage Peak Peak	10 mV to 20 mV class
Ripple Noise Current RMS	less than 5 mA on higher current models class
Transient Recovery	less than 50 us class to within 10 mV
Crowbar Range	approximately 10 percent to 110 percent of rated voltage
DC Floating Voltage	up to 300 V above ground
Front Output Terminal Rating	monitoring only, 3 A maximum
AC Input	115 Vac plus or minus 10 percent, 57 to 63 Hz standard
Cabinet Height	3.5 in full rack
Cooling	convection except forced air on 6274B
Remote Programming	resistance or voltage
Remote Sensing	yes
Auto Parallel	two or three similar supplies
Auto Series	two or three supplies
Metering	front panel voltmeter and ammeter

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications	
Specifications	
PARAMETER	VALUE
Instrument Type	CV/CC regulated DC power supply
Series Family	HP 6256B 6263B 6264B 6265B 6266B 6267B 6271B 6274B
Output Voltage Rating	0 to 20 V
Output Current Rating	0 to 10 A
Operating Modes	constant voltage and constant current with automatic crossover
Load Regulation Voltage	0.01 percent plus 200 uV class
Load Regulation Current	0.02 percent plus milliamp class
Line Regulation Voltage	0.01 percent plus 200 uV class
Line Regulation Current	0.02 percent plus milliamp class
Ripple Noise Voltage RMS	200 uV to 1 mV class by model
Ripple Noise Voltage Peak Peak	10 mV to 20 mV class
Ripple Noise Current RMS	less than 5 mA on higher current models class
Transient Recovery	less than 50 us class to within 10 mV
Crowbar Range	approximately 10 percent to 110 percent of rated voltage
DC Floating Voltage	up to 300 V above ground
Front Output Terminal Rating	monitoring only, 3 A maximum
AC Input	115 Vac plus or minus 10 percent, 57 to 63 Hz standard
Cabinet Height	3.5 in full rack
Cooling	convection except forced air on 6274B
Remote Programming	resistance or voltage
Remote Sensing	yes
Auto Parallel	two or three similar supplies
Auto Series	two or three supplies
Metering	front panel voltmeter and ammeter

Notes

From HP Operating and Service Manual Models 6256B, 6263B, 6264B, 6265B, 6266B, 6267B, 6271B, and 6274B Table 1-1 OUTPUT row for this model only.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 14, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.