

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 14, 2026

AGILENT / KEYSIGHT

Agilent/Keysight 6552A DC Power Supply

Agilent 6552A Analog Programmable DC Power Supply 0 to 20 V 0 to 25 A The Agilent/HP 6552A is a single-output analog-programmable DC power supply. OEM Series 654xA/655xA/657xA operating manual rates 0 to 20 V and 0 to 25 A (500 W). Manufacturing and R&D DC rails with analog programming, OVP, and local/remote sensing. Auto-parallel of identical models on 2000 W class The Agilent/HP 6552A is a single-output analog-programmable DC power supply. OEM Series 654xA/655xA/657xA operating manual rates 0 to 20 V and 0 to 25 A (500 W). Manufacturing and R&D DC rails with analog programming, OVP, and local/remote sensing. Auto-parallel of identical models on 2000 W class Instrument Type: Analog programmable DC power supply



MODEL

**Agilent / Keysight
6552A**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

6552A

LISTING

<https://aumictechlabs.com/products/6552a-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight 6552A Quadrupole Time-of-Flight (Q-TOF) mass spectrometer delivers outstanding performance in various analytical applications. Its advanced Q-TOF technology provides high resolution and mass accuracy, enabling precise identification and quantification of compounds. The instrument is equipped with rapid data acquisition capabilities, making it suitable for high-throughput analyses. Its solid design and user-friendly software interface ensure reliable operation and efficient data processing. Applications include proteomics, metabolomics, food

safety, and environmental analysis, where accurate and comprehensive compound characterization is essential.

6552A Characteristics / Specifications

PARAMETER	VALUE
Instrument Type	Analog programmable DC power supply
Series Family	Agilent 654xA 655xA 657xA
Number of Outputs	1
GPIB Interface	No
Output Voltage Rating	0 to 20 V
Output Current Rating	0 to 25 A
Maximum Power Class	500 W
Current Derating	1 percent perCfrom 40 C to 55 C where stated
Programming Accuracy Voltage 25 C	0.06 percent plus 10 mV
Programming Accuracy Current	0.14 to 0.15 percent plus 25 mA
Ripple Noise Voltage RMS 20 Hz to 20 MHz	300 uV
Ripple Noise Voltage Peak Peak	3 mV
Ripple Noise Current RMS	10 mA
Readback Accuracy Voltage	0.07 percent plus 15 mV
Readback Accuracy Positive Current	0.15 percent plus 26 mA
Transient Response Time	less than 100 us for up to 50 percent load step (654/655); less than 900 us to within 100 mV (657)
DC Floating Voltage	plus or minus 240 Vdc
Remote Sensing	yes
Overvoltage Protection	programmable
Analog Programming VP IP	yes
Current Monitor IM	yes
AC Input	100/120/220/230/240 Vac selectable class
Size Class	500 W chassis
Operating Temperature	0 to 55 C warranted with resistive load

6552A Specifications

PARAMETER	VALUE
Applications	Manufacturing and R&D DC rails with analog programming, OVP, and local/remote sensing.
Key Features	Analog voltage and current programming
Technical Specifications	Instrument Type: Analog programmable DC power supply
Notes	Agilent 654xA/655xA OM Table 1-1a column 6552A.

General Specifications & Supplementary Characteristics

PARAMETER	VALUE
Operating temperature	0 to 55 C warranted with resistive load
Operating Temperature	0 to 55 C warranted with resistive load

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications	
Specifications	
PARAMETER	VALUE
Instrument Type	Analog programmable DC power supply
Series Family	Agilent 654xA 655xA 657xA
Number of Outputs	1
GPiB Interface	No
Output Voltage Rating	0 to 20 V
Output Current Rating	0 to 25 A
Maximum Power Class	500 W
Current Derating	1 percent perCfrom 40 C to 55 C where stated
Programming Accuracy Voltage 25 C	0.06 percent plus 10 mV
Programming Accuracy Current	0.14 to 0.15 percent plus 25 mA
Ripple Noise Voltage RMS 20 Hz to 20 MHz: 300 uV	
Specifications	
PARAMETER	VALUE
Ripple Noise Voltage Peak Peak	3 mV
Ripple Noise Current RMS	10 mA
Readback Accuracy Voltage	0.07 percent plus 15 mV
Readback Accuracy Positive Current	0.15 percent plus 26 mA
Transient Response Time	less than 100 us for up to 50 percent load step (654/655); less than 900 us to within 100 mV (657)
DC Floating Voltage	plus or minus 240 Vdc
Remote Sensing	yes
Overvoltage Protection	programmable
Analog Programming VP IP	yes
Current Monitor IM	yes
AC Input	100/120/220/230/240 Vac selectable class
Size Class	500 W chassis

PARAMETER

VALUE

Operating Temperature

0 to 55 C warranted with resistive load

Notes

Agilent 654xA/655xA OM Table 1-1a column 6552A.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 14, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.