

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

AGILENT / KEYSIGHT

Agilent/Keysight MXR108A

Keysight Infiniium MXR108A Real Time Oscilloscope 1 GHz 8 Channel The Keysight Infiniium MXR108A is an MXR-Series real-time oscilloscope with 1 GHz analog bandwidth (-3 dB) on the 50 ohm path and 8 analog channels. The OEM Infiniium MXR-Series data sheet lists 16 GSa/s sample rate on every channel, 200 Mpts standard memory per channel, 10 bit vertical resolution (up to 16 bits in high-resolution mode), timebase accuracy of 8 ppb, intrinsic jitter as low as 118 fs, and a 15.6 inch full HD touch display. The Keysight Infiniium MXR108A is an MXR-Series real-time oscilloscope with 1 GHz analog bandwidth (-3 dB) on the 50 ohm path and 8 analog channels. The OEM Infiniium MXR-Series data sheet lists 16 GSa/s sample rate on every channel, 200 Mpts standard memory per channel, 10 bit vertical resolution (up to 16 bits in high-resolution mode), timebase accuracy of 8 ppb, intrinsic jitter as low as 118 fs, and a 15.6 inch full HD touch display. High-speed digital debug, power integrity and rail analysis, protocol decode, compliance testing, and multi-channel RF analysis with optional RTSA/DDC on the Infiniium MXR platform.

**MODEL****Agilent / Keysight
MXR108A****CALIBRATION****Available on
request****CONDITION****Used****STATUS****In stock****RFQ / SKU****MXR108A****LISTING**<https://aumictechlabs.com/products/mxr108a-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight MXR108A is a real-time oscilloscope engineered for high-speed digital signal integrity measurements and advanced debugging applications. Built on UXR-Series hardware

acceleration ASICs, it delivers 8 analog channels at 1 GHz bandwidth and 16 GSa/s per channel, with triggering and eye diagram analysis optimized for demanding measurements. The instrument supports mixed-signal operation with an optional MSO license enabling 16 digital input channels at 8 GSa/s, plus configurable memory from 200 Mpts to 1.6 Gpts flexible architecture.

Technical Specifications

Bandwidth: 1 GHz

Analog Channels: 8 (upgradeable to 8 + 16 with MSO license)

Digital Channels: 16 input channels (MSO license required); 8 GSa/s sample rate

Sample Rate: 16 GSa/s per analog channel

Memory Depth: 200 Mpts standard; upgradeable to 400 Mpts or 1.6 Gpts total flexible memory

ADC Resolution: 10-bit native; up to 16-bit high-resolution mode

Timebase Accuracy: 8 parts per billion

Input Noise: 43 μ V minimum at 1 mV/div

ENOB: Up to 9.0

Waveform Update Rate: >200,000 waveforms/second

Display: 15.6-inch capacitive touch screen, 1920×1080 FHD, multi-touch gestures

Operating System: 64-bit Windows

Key Features

- Flexible three-stage triggering with InfiniiScan advanced and zone triggering (standard)
- Over 50 automated measurements and statistics
- Hardware acceleration for eye plots and triggering
- Fault Hunter analysis capability
- History Mode: capture up to 1,024 previous trigger events (standard)
- Segmented Memory: record >100,000 post-trigger events

Integrated Instruments & Functions

- Logic Analyzer
- Protocol Analyzer with decode and search
- Real-Time Spectrum Analyzer (RTSA) mode
- Frequency Response Analyzer
- Digital Voltmeter (DVM)
- Triple Counters with totalizer
- Waveform Generator
- Power Analysis tools

Connectivity & Integration

USB 3.0, LAN, VGA, and DisplayPort interfaces

BNC output for waveform generation

Native Windows OS enables third-party application integration

MXR108A Characteristics / Specifications

PARAMETER	VALUE
Model	MXR108A
Instrument Family	Infiniium MXR-Series
Analog Bandwidth Fifty Ohm	1 GHz
Analog Bandwidth One Megohm	500 MHz
Analog Channels	8
Digital Logic Channels	16 optional via MXR2MSO
Sample Rate Real Time	16 GSa/s all analog channels
Sample Resolution	62.5 ps
Vertical Resolution	10 bits up to 16 bits high resolution mode
Standard Memory Depth	200 Mpts per channel
Extended Memory Depth	400 Mpts per channel or 1.6 Gpts combined flexible memory
Real Time Update Rate	greater than 200000 waveforms per second
Eye Diagram Plot Rate	greater than 750000 UI per second
Timebase Accuracy	8 ppb initial plus 75 ppb per year aging
Intrinsic Jitter Four Channel Models	118 fs rms at 100 ns/div
Intrinsic Jitter Eight Channel Models	150 fs rms at 100 ns/div
Inter Channel Intrinsic Jitter	100 fs rms
Lowest Noise One Millivolt Per Division	as low as 43 uV (20 MHz high resolution path)
Rms Noise Floor At Model Bandwidth	73 uV at 1 mV/div on 50 ohm inputs
Effective Number Of Bits At Model Bandwidth	8.0 at 50 mV/div on 50 ohm inputs
Typical Rise Time Ten Ninety	430 ps
Typical Rise Time Twenty Eighty	310 ps
Input Impedance Fifty Ohm	50 ohm plus or minus 3.5 percent
Input Impedance One Megohm	1 Mohm plus or minus 1 percent (14 pF typical)
Input Sensitivity Fifty Ohm	1 mV/div to 1 V/div

PARAMETER	VALUE
Input Sensitivity One Megohm	1 mV/div to 5 V/div
Max Input Voltage Fifty Ohm	plus or minus 5 V max
Max Input Voltage One Megohm	30 Vrms or plus or minus 40 V max
Dc Gain Accuracy	plus or minus 2 percent full scale (plus or minus 1 percent typical)
Channel Isolation Adjacent Dc To Two Gigahertz	less than or equal to -60 dB
Display	15.6 inch touch full HD 1920×1080 with dual screen support
Waveform Generator Bandwidth	50 MHz with MXR2WAV
Rtsa Analysis Bandwidth Standard	40 MHz
Rtsa Analysis Bandwidth Extended	160 MHz or 320 MHz with MXR2RTSA
Dimensions Height	327.5 mm (12.9 in)
Dimensions Width	444.5 mm (17.5 in)
Dimensions Depth	224.1 mm (8.85 in)
History Mode Depth	up to 1024 previous acquisitions
Segmented Memory Acquisitions	up to 78953 future acquisitions
Max Edge Trigger Frequency	6 GHz on 50 ohm path
Digital Channel Bandwidth	300 MHz with MSO
Digital Channel Sample Rate	8 GSa/s with MSO
Bandwidth	Fifty Ohm: 1 GHz
Rise Time	Ten Ninety: 430 ps

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications	
Specifications	
PARAMETER	VALUE
Model	MXR108A
Instrument Family	Infiniium MXR-Series
Analog Bandwidth Fifty Ohm	1 GHz
Analog Bandwidth One Megohm	500 MHz
Analog Channels	8
Digital Logic Channels	16 optional via MXR2MSO
Sample Rate Real Time	16 GSa/s all analog channels
Sample Resolution	62.5 ps
Vertical Resolution	10 bits up to 16 bits high resolution mode
Standard Memory Depth	200 Mpts per channel
Extended Memory Depth	400 Mpts per channel or 1.6 Gpts combined flexible memory
Real Time Update Rate	greater than 200000 waveforms per second
Eye Diagram Plot Rate	greater than 750000 UI per second
Timebase Accuracy	8 ppb initial plus 75 ppb per year aging
Intrinsic Jitter Four Channel Models	118 fs rms at 100 ns/div
Intrinsic Jitter Eight Channel Models	150 fs rms at 100 ns/div
Inter Channel Intrinsic Jitter	100 fs rms
Lowest Noise One Millivolt Per Division	as low as 43 uV (20 MHz high resolution path)
Rms Noise Floor At Model Bandwidth	73 uV at 1 mV/div on 50 ohm inputs
Effective Number Of Bits At Model Bandwidth	8.0 at 50 mV/div on 50 ohm inputs
Typical Rise Time Ten Ninety	430 ps
Typical Rise Time Twenty Eighty	310 ps
Input Impedance Fifty Ohm	50 ohm plus or minus 3.5 percent
Input Impedance One Megohm	1 Mohm plus or minus 1 percent (14 pF typical)
Input Sensitivity Fifty Ohm	1 mV/div to 1 V/div

PARAMETER	VALUE
Input Sensitivity One Megohm	1 mV/div to 5 V/div
Max Input Voltage Fifty Ohm	plus or minus 5 V max
Max Input Voltage One Megohm	30 Vrms or plus or minus 40 V max
Dc Gain Accuracy	plus or minus 2 percent full scale (plus or minus 1 percent typical)
Channel Isolation Adjacent Dc To Two Gigahertz	less than or equal to -60 dB
Display	15.6 inch touch full HD 1920x1080 with dual screen support
Waveform Generator Bandwidth	50 MHz with MXR2WAV
Rtsa Analysis Bandwidth Standard	40 MHz
Rtsa Analysis Bandwidth Extended	160 MHz or 320 MHz with MXR2RTSA
Dimensions Height	327.5 mm (12.9 in)
Dimensions Width	444.5 mm (17.5 in)
Dimensions Depth	224.1 mm (8.85 in)
History Mode Depth	up to 1024 previous acquisitions
Segmented Memory Acquisitions	up to 78953 future acquisitions
Max Edge Trigger Frequency	6 GHz on 50 ohm path
Digital Channel Bandwidth	300 MHz with MS0
Digital Channel Sample Rate	8 GSa/s with MS0

Notes

Bandwidth, channel count, rise/fall times, sample rate, memory, noise, ENOB, timebase, jitter, input ranges, display size, and dimensions from the Keysight Infiniium MXR-Series data sheet performance characteristics and model number table (MXR05xA through MXR60xA rows). Model MXR108A uses the MXR family row matching 1 GHz bandwidth.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.