


Aumictech

Test & measurement · bought, sold, repaired, calibrated


Data Sheet

August 14, 2026

AGILENT / KEYSIGHT

Agilent/Keysight PA2201A

The Agilent/Keysight PA2201A is a PA2200 Series IntegraVision power analyzer combining 0.05 percent basic accuracy with touch-driven waveform visualization. OEM data sheet 5992-0324EN lists 5 MSa/s 16-bit digitizing, 1000 Vrms CAT II isolated inputs, and 2 channels. AC/DC power conversion, inverter efficiency, UPS energy storage, EV/HEV inverters, and IEC 61000-3-2 harmonic pre-compliance. Oscilloscope-style single-shot capture of inrush and line dropouts Continuous Whole-Cycle Analysis without measurement gaps Dimensions WxHxD: 426 mm x 308 mm x 272.8 mm Remote Interfaces: USB 2.0 hi-speed device USBTMC and 10/100/1000 Base-T LAN Reference Input: 10 MHz earth-referenced SMA; 0 to 3.3 V logic (5 V max) Numeric rows from Keysight IntegraVision PA2200 Series Power Analyzers data sheet 5992-0324EN model PA2201A.



MODEL

**Agilent / Keysight
PA2201A**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

PA2201A

LISTING

<https://aumictechlabs.com/products/pa2201a-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Keysight PA2201A IntegraVision Power Analyzer combines oscilloscope and power analyzer functionality in a single instrument for precise AC, DC, and AC+DC power measurements. Engineers gain simultaneous voltage, current, and power waveform capture with 16-bit resolution across two measurement channels, enabling real-time insight into power consumption, conversion efficiency, and dynamic performance. The dual-channel architecture supports single-

phase AC and balanced three-phase applications, with basic accuracy of 0.05% at 50/60 Hz and true RMS calculations even with non-sinusoidal waveforms and DC offsets.

Technical Specifications

Measurement Architecture 2 channels with simultaneous voltage, current, and power measurement 16-bit resolution across all waveforms 5 MSamples/second sampling rate with up to 4M point record length per waveform Basic accuracy: 0.05% at 50/60 Hz Voltage and Current Ranges Maximum AC voltage: 1000 Vrms Maximum AC current: 50 A (internal shunts) Supports external current probes and transducers Bandwidth and Frequency Response Voltage: up to 2 MHz Current (internal shunts): up to 100 kHz for 2 Arms and 50 Arms shunts External current probes: up to 2.5 MHz with 10 V full-scale output Timebase: 50 s/div to 20 μ s/div Power Quality and Harmonic Analysis Power measurements: Watts, VA, VAR, power factor, phase angle Crest factor analysis for voltage and current FFT and harmonic measurements with IEC 61000-3-2 compliance (Classes A, B, C, D) Transient Capture and Triggering Single-shot mode for power transient analysis Edge triggering on voltage, current, or power signals Trigger I/O: 0 to 3.3 V logic level (5 V max) 10 MHz reference input

Key Features 12.1-inch high-resolution LCD touchscreen display Isolated, floating inputs to 1000 V (Cat II) USB 2.0 host and device ports LAN connectivity with web remote control

Typical Applications Power conversion systems, electric vehicle characterization, aerospace power distribution validation, and R&D design verification requiring simultaneous waveform and power quality analysis.

Compatibility & Integration USB 2.0 hi-speed connectivity, LAN interface with web-based remote control, and standard triggering support enable integration into automated test environments.

PA2201A Characteristics / Specifications

PARAMETER	VALUE
Instrument Type	IntegraVision power analyzer with oscilloscope-style visualization
Series Family	Keysight PA2200 Series
Power Channels	2 channels
Phase Application	single-phase and balanced three-phase
Basic Accuracy 50 60 Hz	0.05 percent of reading
Best Power Accuracy 50 60 Hz	0.1 percent of reading
Voltage Accuracy 40 to 100 Hz	0.05 percent of reading plus 0.05 percent of range; fixed term 100 μ V
Digitizer Rate	maximum 5 M samples per second at 16 bits on each waveform simultaneously
Analog Bandwidth	2.5 MHz (anti-aliasing filter off, minus 3 dB at or above 2.5 MHz)
Voltage Measurement Bandwidth	specified to 1 MHz
Current Direct Bandwidth	specified to 100 kHz on 2 A or 50 A inputs
Current External Bandwidth	specified to 1 MHz
Maximum Voltage	1000 Vrms (2000 Vpeak; peak not to exceed 25 ms)
Voltage Ranges	5 V, 10 V, 20 V, 50 V, 100 V, 200 V, 500 V, 1000 V
Voltage Input Impedance	2 MOhm parallel 12.5 pF
Direct Current 2 A Path	2 Arms, 6 A peak; ranges 10 mA to 2 A
Direct Current 50 A Path	50 Arms, 100 A peak; ranges 200 mA to 50 A
Shunt Impedance 2 A	60 mOhm plus 0.10 μ H
Shunt Impedance 50 A	6 mOhm plus 0.06 μ H
External Transducer Input	10 Vrms 30 Vpeak isolated BNC; 100 kOhm parallel 100 pF
External Transducer Ranges	50 mV, 100 mV, 200 mV, 500 mV, 1 V, 2 V, 5 V, 10 V
Record Size	maximum 1.5 M points on each waveform simultaneously
Timebase	50 s/div (500 seconds) maximum; 20 μ s/div (200 μ s) minimum
Harmonic Orders	up to 250 orders (attainable below 120 Hz fundamental)
Harmonic Frequency Limit	less than 30 kHz for any order

PARAMETER	VALUE
THD Residual	minus 75 dBc at full scale for all inputs (less than 10 kHz)
Crest Factor Full Scale	3 at full scale unless in conflict with maximum ratings
Isolation Rating	1000 V CAT II voltage and current terminals to earth and to each other
Display	12.1 inch capacitive multi-touch 800 × 600
Power Line Consumption	maximum 180 VA
AC Line	100 to 240 V 50/60 Hz plus or minus 10 percent; 100 to 120 V also 400 Hz; auto ranging
Operating Temperature	0 to plus 40 C
Storage Temperature	minus 40 to plus 70 C
Humidity Operating	80 percent RH non-condensing at 40 C
Altitude Operating	up to 3000 m
Warm Up Time	60 minutes
Calibration Cycle	1 year
Logging Interval	50 ms to 1 day
Logging Duration	1 s to 1 year
Trigger Jitter	plus or minus 100 ns
Dimensions WxHxD	426 mm x 308 mm x 272.8 mm
Weight Net	11.4 kg (25.2 lb)
Weight Shipping	12.8 kg (28.3 lb)
Remote Interfaces	USB 2.0 hi-speed device USBTMC and 10/100/1000 Base-T LAN
Reference Input	10 MHz earth-referenced SMA; 0 to 3.3 V logic (5 V max)
Bandwidth	2.5 MHz (anti-aliasing filter off, minus 3 dB at or above 2.5 MHz)
Humidity	Operating: 80 percent RH non-condensing at 40 C

General Specifications & Supplementary Characteristics

PARAMETER	VALUE
Storage temperature	minus 40 to plus 70 C
Operating temperature	0 to plus 40 C
Operating Temperature	0 to plus 40 C
Humidity	Operating: 80 percent RH non-condensing at 40 C
Humidity Operating	80 percent RH non-condensing at 40 C
Altitude Operating	up to 3000 m
Warm Up Time	60 minutes
Calibration Cycle	1 year
Logging Interval	50 ms to 1 day
Logging Duration	1 s to 1 year
Trigger Jitter	plus or minus 100 ns
Dimensions WxHxD	426 mm x 308 mm x 272.8 mm
Weight Net	11.4 kg (25.2 lb)
Weight Shipping	12.8 kg (28.3 lb)
Remote Interfaces	USB 2.0 hi-speed device USBTMC and 10/100/1000 Base-T LAN
Reference Input	10 MHz earth-referenced SMA; 0 to 3.3 V logic (5 V max) Notes Numeric rows from Keysight IntegraVision PA2200 Series Power Analyzers data sheet 5992-0324EN model PA2201A.

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications	
Specifications	
PARAMETER	VALUE
Instrument Type	IntegraVision power analyzer with oscilloscope-style visualization
Series Family	Keysight PA2200 Series
Power Channels	2 channels
Phase Application	single-phase and balanced three-phase
Basic Accuracy 50 60 Hz	0.05 percent of reading
Best Power Accuracy 50 60 Hz	0.1 percent of reading
Voltage Accuracy 40 to 100 Hz	0.05 percent of reading plus 0.05 percent of range; fixed term 100 uV
Digitizer Rate	maximum 5 M samples per second at 16 bits on each waveform simultaneously
Analog Bandwidth	2.5 MHz (anti-aliasing filter off, minus 3 dB at or above 2.5 MHz)
Voltage Measurement Bandwidth	specified to 1 MHz
Current Direct Bandwidth	specified to 100 kHz on 2 A or 50 A inputs
Current External Bandwidth	specified to 1 MHz
Maximum Voltage	1000 Vrms (2000 Vpeak; peak not to exceed 25 ms)
Voltage Ranges	5 V, 10 V, 20 V, 50 V, 100 V, 200 V, 500 V, 1000 V
Voltage Input Impedance	2 MOhm parallel 12.5 pF
Direct Current 2 A Path	2 Arms, 6 A peak; ranges 10 mA to 2 A
Direct Current 50 A Path	50 Arms, 100 A peak; ranges 200 mA to 50 A
Shunt Impedance 2 A	60 mOhm plus 0.10 uH
Shunt Impedance 50 A	6 mOhm plus 0.06 uH
External Transducer Input	10 Vrms 30 Vpeak isolated BNC; 100 kOhm parallel 100 pF
External Transducer Ranges	50 mV, 100 mV, 200 mV, 500 mV, 1 V, 2 V, 5 V, 10 V
Record Size	maximum 1.5 M points on each waveform simultaneously
Timebase	50 s/div (500 seconds) maximum; 20 us/div (200 us) minimum
Harmonic Orders	up to 250 orders (attainable below 120 Hz fundamental)
Harmonic Frequency Limit	less than 30 kHz for any order

PARAMETER	VALUE
THD Residual	minus 75 dBc at full scale for all inputs (less than 10 kHz)
Crest Factor Full Scale	3 at full scale unless in conflict with maximum ratings
Isolation Rating	1000 V CAT II voltage and current terminals to earth and to each other
Display	12.1 inch capacitive multi-touch 800 x 600
Power Line Consumption	maximum 180 VA
AC Line	100 to 240 V 50/60 Hz plus or minus 10 percent; 100 to 120 V also 400 Hz; auto ranging
Operating Temperature	0 to plus 40 C
Storage Temperature	minus 40 to plus 70 C
Humidity Operating	80 percent RH non-condensing at 40 C
Altitude Operating	up to 3000 m
Warm Up Time	60 minutes
Calibration Cycle	1 year
Logging Interval	50 ms to 1 day
Logging Duration	1 s to 1 year
Trigger Jitter	plus or minus 100 ns
Dimensions WxHxD	426 mm x 308 mm x 272.8 mm
Weight Net	11.4 kg (25.2 lb)
Weight Shipping	12.8 kg (28.3 lb)
Remote Interfaces	USB 2.0 hi-speed device USBTMC and 10/100/1000 Base-T LAN
Reference Input	10 MHz earth-referenced SMA; 0 to 3.3 V logic (5 V max)

Notes

Numeric rows from Keysight IntegraVision PA2200 Series Power Analyzers data sheet 5992-0324EN model PA2201A.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 14, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.