

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 14, 2026

AGILENT / KEYSIGHT

Agilent N6746b, Dc Power Module, 100v, 1a, 100w

Agilent Keysight N6746B Basic DC Power Module 100 V 1 A 100 W The Agilent/Keysight N6746B is a 100 W basic DC power module for N6700/N6705 mainframes rated 0 to 100 V / 0 to 1 A / 100 W. OEM N6700 Modular Power System Family datasheets list ripple noise programming accuracy and measurement accuracy for this model row. ATE and R&D DC rails needing 100 W at up to 100 V in a single N6700/N6705 slot. Optional output disconnect relays Option 761 The Agilent/Keysight N6746B is a 100 W basic DC power module for N6700/N6705 mainframes rated 0 to 100 V / 0 to 1 A / 100 W. OEM N6700 Modular Power System Family datasheets list ripple noise programming accuracy and measurement accuracy for this model row. ATE and R&D DC rails needing 100 W at up to 100 V in a single N6700/N6705 slot. Optional output disconnect relays Option 761 Compatible with N6700 and N6705 mainframes



MODEL

**Agilent / Keysight
N6746B**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

N6746B

LISTING

<https://aumictechlabs.com/products/n6746b-3/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight N6746B is a precision DC power module offering exceptional performance. Key features include programmable voltage and current, high accuracy, and low ripple and noise. It supports various programming interfaces for seamless integration into automated test systems.

The N6746B ensures stable and repeatable power delivery, essential for critical testing and development processes.

N6746B Characteristics / Specifications

PARAMETER	VALUE
Model	N6746B
DC Output Voltage	0 to 100 V
DC Output Current	0 to 1 A
DC Output Power	100 W
Ripple Noise Voltage Peak To Peak	30 mV
Ripple Noise Voltage RMS	18 mV
Voltage Programming Accuracy	0.1 percent + 100 mV
Current Programming Accuracy	0.15 percent + 10 mA
Voltage Measurement Accuracy	0.1 percent + 100 mV
Current Measurement Accuracy	0.15 percent + 2 mA
Mainframe Compatibility	N6700 and N6705 series
Slot Occupancy	1 of 4 slots
Arbitrary Waveform Generation	Yes
Output Disconnect Relays Option	Option 761
Polarity Reversal Relays Option	Option 760 (current limited on some models per OEM note)
Series Family	Keysight N6700 basic DC modules
Module Class	100 W basic
PARD Bandwidth	20 Hz to 20 MHz
Programming Accuracy Temperature	23 C plus or minus 5 C after 30 minute warm-up class family
Load Effect Voltage	20 mV / 30 mV class OEM 50W/100W column
Load Effect Current	2 mA
Source Effect Voltage	10 mV
Source Effect Current	1 mA
Load Transient Recovery Time	less than 200 us
Measurement Data Points Default	1024

PARAMETER	VALUE
Measurement Time Interval Default	20.48 us
Current Derating Above 40 C	1 percent perCOutput Isolation: floating isolated from chassis ground class family
Bandwidth	20 Hz to 20 MHz
Output isolation	floating isolated from chassis ground class family

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance DC power module
Occupies one mainframe slot
Arbitrary waveform generation capable
Optional output disconnect relays Option 761
Compatible with N6700 and N6705 mainframes

Technical Specifications

PARAMETER	VALUE
Model	N6746B
DC Output Voltage	0 to 100 V
DC Output Current	0 to 1 A
DC Output Power	100 W
Ripple Noise Voltage Peak To Peak	30 mV
Ripple Noise Voltage RMS	18 mV
Voltage Programming Accuracy	0.1 percent + 100 mV
Current Programming Accuracy	0.15 percent + 10 mA
Voltage Measurement Accuracy	0.1 percent + 100 mV
Current Measurement Accuracy	0.15 percent + 2 mA
Mainframe Compatibility	N6700 and N6705 series
Slot Occupancy	1 of 4 slots
Arbitrary Waveform Generation	Yes
Output Disconnect Relays Option	Option 761
Polarity Reversal Relays Option	Option 760 (current limited on some models per OEM note)
Series Family	Keysight N6700 basic DC modules
Module Class	100 W basic
PARD Bandwidth	20 Hz to 20 MHz
Programming Accuracy Temperature	23 C plus or minus 5 C after 30 minute warm-up class family
Load Effect Voltage	20 mV / 30 mV class OEM 50W/100W column
Load Effect Current	2 mA
Source Effect Voltage	10 mV
Source Effect Current	1 mA

PARAMETER	VALUE
Load Transient Recovery Time	less than 200 us
Measurement Data Points Default	1024
Measurement Time Interval Default	20.48 us
Current Derating Above 40 C	1 percent perCOutput Isolation: floating isolated from chassis ground class family

Notes
From Keysight N6700 Modular Power System Family Data Sheet DC Power Module Key Performance Specifications row for N6746B. Option 760 limits output current to 10 A maximum on N6773A per OEM note.

Ordering Information

OPTION	DESCRIPTION
Option 761	Compatible with N6700 and N6705 mainframes
Option 760	limits output current to 10 A maximum on N6773A per OEM note.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech
788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 14, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.