

**Aumictech**

Test & measurement • bought, sold, repaired, calibrated

Data Sheet

August 1, 2026

ANRITSU

Anritsu 68055B Synthesized CW Generator

Dimensions: about 5.25 inHx 16.875 inWx 23.5 inDWeight: about 50 lb class 11 Fine frequency resolution; 15 High power; 16 High-stability ovenized crystal timebase; step attenuator; rack mount Allow warm-up for frequency accuracy, especially with Option 16 oven. Use appropriate coax adapters for the installed RF connector. Do not exceed leveled power into sensitive receivers without attenuation. Correct spelling is Anritsu (user "Anrtisu"). Confirm Option 15 before quoting high-power levels. CW-only 68055B does not include analog sweep. 11 Fine frequency resolution; 15 High power; 16 High-stability ovenized crystal timebase; step attenuator; rack mount Allow warm-up for frequency accuracy, especially with Option 16 oven. Use appropriate coax adapters for the installed RF connector. Do not exceed leveled power into sensitive receivers without attenuation. Correct spelling is Anritsu (user "Anrtisu"). Confirm Option 15 before quoting high-power levels. CW-only 68055B does not include analog sweep.

No photo

MODEL

Anritsu 68055B

CALIBRATION

**N/A — off-catalog
OEM datasheet**

CONDITION

**See OEM
documentation**

STATUS

**Not listed on
Aumictech
inventory**

RFQ / SKU

68055B

LISTING

**Off-catalog — OEM dat
asheet only**

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 • 811210 • 541380

Features & description

From manufacturer datasheet

Features

- Frequency range 0.5 GHz to 26.5 GHz
- Synthesized CW operation with high-resolution phase lock
- Standard frequency resolution 1 kHz; Option 11 for 0.1 Hz class resolution
- Leveled output power to +13 dBm (0.5-2.2 GHz), +9 dBm (above 2.2-20 GHz), and +6 dBm (20-26.5 GHz) without step attenuator
- Optional high-power output (Option 15) and high-stability oven timebase (Option 16)
- Optional step attenuator
- Front-panel LCD with rotary knob and keypad
- IEEE-488 / GPIB remote control of all functions except power on/standby

68055B Characteristics / Specifications

PARAMETER	VALUE
Model	68055B
Manufacturer	Anritsu / Wiltron
Series	680XXB Synthesized CW Generators
Instrument Type	Synthesized CW microwave signal generator
Frequency Range	0.5 GHz to 26.5 GHz
Frequency Resolution	1 kHz standard; 0.1 Hz with Option 11
Above 2.2 to 20 GHz	+9 dBm 20 to 26.5 GHz: +6 dBm
With step attenuator	about +11 dBm (0.5-2.2 GHz); +7 dBm (above 2.2-20 GHz); +3.5 dBm (20-26.5 GHz)
With Option 15 (high power)	about +13 dBm across 0.5 to 20 GHz class (datasheet Option 15 table) Spectral Purity (680XXB family examples at carrier) SSB phase noise examples scale with carrier frequency per Anritsu 68B/69A datasheet tables General
Dimensions	about 5.25 inHx 16.875 inWx 23.5 inDWeight: about 50 lb class
Remote Interface	IEEE-488 (GPIB)
Display	Dot-matrix LCD Common Options 11 Fine frequency resolution; 15 High power; 16 High-stability ovenized crystal timebase; step attenuator; rack mount Family Context 68045B: 0.5 to 20 GHz CW 68053B: 2 to 26.5 GHz CW 68055B: 0.5 to 26.5 GHz CW 68059B: 10 MHz to 26.5 GHz CW

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications

Specifications

PARAMETER	VALUE
Dimensions	about 5.25 in H x 16.875 in W x 23.5 in D
Weight	about 50 lb class
Remote Interface	IEEE-488 (GPIB)
Display	Dot-matrix LCD

Specifications

PARAMETER	VALUE
Model	68055B
Manufacturer	Anritsu / Wiltron
Series	680XXB Synthesized CW Generators
Instrument Type	Synthesized CW microwave signal generator
Frequency Range	0.5 GHz to 26.5 GHz
Frequency Resolution	1 kHz standard; 0.1 Hz with Option 11

RF Output Power (standard, without step attenuator) – 6XX55 class
0.5 to 2.2 GHz: +13 dBm
Above 2.2 to 20 GHz: +9 dBm
20 to 26.5 GHz: +6 dBm
With step attenuator: about +11 dBm (0.5-2.2 GHz); +7 dBm (above 2.2-20 GHz); +3.5 dBm (20-26.5 GHz)
With Option 15 (high power): about +13 dBm across 0.5 to 20 GHz class (datasheet Option 15 table)

Spectral Purity (680XXB family examples at carrier)
SSB phase noise examples scale with carrier frequency per Anritsu 68B/69A datasheet tables

General

Specifications

PARAMETER	VALUE
Dimensions	about 5.25 inHx 16.875 inWx 23.5 inDWeight: about 50 lb class
Remote Interface	IEEE-488 (GPIB)
Display	Dot-matrix LCD

Common Options
11 Fine frequency resolution; 15 High power; 16 High-stability ovenized crystal timebase; step attenuator; rack mount

Family Context

68045B: 0.5 to 20 GHz CW

68053B: 2 to 26.5 GHz CW

68055B: 0.5 to 26.5 GHz CW

68059B: 10 MHz to 26.5 GHz CW

Standard Operating Conditions

Allow warm-up for frequency accuracy, especially with Option 16 oven. Use appropriate coax adapters for the installed RF connector. Do not exceed leveled power into sensitive receivers without attenuation.

Operational Notes

Correct spelling is Anritsu (user "Anrtisu"). Confirm Option 15 before quoting high-power levels. CW-only 68055B does not include analog sweep.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: N/A — off-catalog OEM datasheet. See OEM documentation · Not listed on Aumictech inventory.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 1, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.