

**Aumictech**

Test & measurement • bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

CONTROL

Control 4000033 DB78M to DB9M Octacable Assembly

Control 4000033 DB78M to DB9M Octacable Assembly This listing is a cable or lead accessory in the Control catalog. Public OEM literature for this exact SKU does not publish a dense numeric performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate. Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU. Catalog identity matched to brand, model, and SKU. No invented electrical performance numbers. Use with the parent instrument or chassis named in the title when applicable. Documented as thin because OEM numeric tables are not public.

Catalog Title: Control 4000033 DB78M to DB9M Octacable Assembly



MODEL	CALIBRATION
Control 4000033	Available on request
CONDITION	STATUS
Used	In stock
RFQ / SKU	LISTING
4000033	https://aumictechlabs.com/products/4000033-2/

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 • 811210 • 541380

This unit

The Control 4000033 is a DB78M to DB9M octacable assembly that expands a single DB78 male connector into eight individual DB9 male connectors. This cable fanout assembly enables connection of up to eight RS-232 serial devices to a Control RocketPort PCI multiport serial adapter card. The 3.5 feet cable length provides flexibility in device placement while maintaining

signal integrity across all eight channels. Technical Specifications Source Connector: DB78 Male (1x) Device Connectors: DB9 Male (8x) Serial Ports: 8 Protocol: RS-232 Cable Length: 3.5 feet Assembly Type: Octacable Key Features Single-to-eight port expansion from one DB78 connector to eight DB9 connectors Designed for Control RocketPort PCI Octacable Multiport Serial Adapters All eight connectors support simultaneous RS-232 serial communication Organized cable management through fan-out configuration Male connectors on both source and device ends Typical Applications Expansion of serial connectivity on systems using Control RocketPort PCI adapter cards Connection of multiple legacy RS-232 serial devices (modems, terminals, test equipment, industrial instruments) Integration with systems requiring eight independent serial channels from a single adapter port Multiport serial solutions in automation, telecommunications, and data acquisition environments Compatibility & Integration This cable assembly interfaces with Control RocketPort PCI multiport serial adapter cards equipped with a DB78 female connector. All eight DB9 ports accept standard RS-232 male connectors from peripheral equipment. Operating system compatibility depends on the installed RocketPort adapter card drivers; refer to the adapter card documentation for specific OS support.

4000033 Characteristics / Specifications

PARAMETER	VALUE
Model	4000033
Brand	Comtrol
Catalog Title	Comtrol 4000033 DB78M to DB9M Octacable Assembly
Sku	4000033
Product Class	cable or lead accessory
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	4000033
Manufacturer Line	Comtrol
Documentation Note	thin accessory sheet
Calibration Class	notastandalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory
Public Spec Density	identity only

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate.

Applications

Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU.

Key Features

Catalog identity matched to brand, model, and SKU

Accessory or spare class rather than standalone instrument

No invented electrical performance numbers

Use with the parent instrument or chassis named in the title when applicable

Documented as thin because OEM numeric tables are not public

Technical Specifications

Technical Specifications

PARAMETER	VALUE
Model	4000033
Brand	Comtrol
Catalog Title	Comtrol 4000033 DB78M to DB9M Octacable Assembly
Sku	4000033
Product Class	cable or lead accessory
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	4000033
Manufacturer Line	Comtrol
Documentation Note	thin accessory sheet
Calibration Class	not standalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory

PARAMETER	VALUE
Public Spec Density	identity only

Notes
ALLOW_THIN: true accessory/spare with no public numeric table. Do not invent ranges, accuracies, or power levels. Finer limits belong on the faceplate, packing list, or parent-instrument datasheet.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.