

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

DEWALT

Dewalt D25651

DeWalt D25651 1-3/4 inch SDS Max Spline Combination Hammer The DeWalt D25651 is a corded 1-3/4 in (45 mm) SDS-Max / spline combination hammer in the D25602/D25651 family. OEM D25651 listings and the D25651/D25851 combination-hammer manual list a 13.5 A motor, 8.0 J (9.5 ft-lb) impact energy, no-load 210 to 415 rpm, 1430 to 2840 bpm, two-stage CTC clutch, SHOCKS active vibration control with 9.1 m/s² published vibration, 18.6 in tool length, and 15.5 lb tool mass, with hammerdrill and chipping modes plus trigger lock-on. The DeWalt D25651 is a corded 1-3/4 in (45 mm) SDS-Max / spline combination hammer in the D25602/D25651 family. OEM D25651 listings and the D25651/D25851 combination-hammer manual list a 13.5 A motor, 8.0 J (9.5 ft-lb) impact energy, no-load 210 to 415 rpm, 1430 to 2840 bpm, two-stage CTC clutch, SHOCKS active vibration control with 9.1 m/s² published vibration, 18.6 in tool length, and 15.5 lb tool mass, with hammerdrill and chipping modes plus trigger lock-on. Concrete drilling and chipping in construction and plant maintenance where a 45 mm SDS-Max or spline combination hammer with bind-up clutch and vibration control is specified.



MODEL

DeWalt D25651

CALIBRATION

Available on request

CONDITION

Used

STATUS

In stock

RFQ / SKU

D25651

LISTING

<https://aumictechlabs.com/products/d25651-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The DeWalt D25651 is a powerful and durable SDS Max combination hammer engineered for heavy-duty drilling and demolition tasks. This tool works with professional use in demanding applications, offering high performance and reliability. Technical Specifications * Motor Power:

13.5 Amp Impact Energy: 9.5 ft-lbs or 8.0 Joules No-Load Speed: 210 - 415 RPM Blows Per Minute (BPM): 1430 - 2840 BPM Chuck Type: SDS Max and Spline Combination Maximum Drilling Capacity (Concrete): * With standard bits: 1-3/4 inch (45 mm) * With core bits: Up to 4 inches (100 mm) Optimal Concrete Drilling Range: 1/2" - 1-3/8" Tool Weight: 15.5 lbs Tool Length: 18.6 inches Power Source: Corded Electric Voltage: 120v Key Features and Technologies * SHOCKS – Active Vibration Control®: Reduces vibration by up to 50% at the handles, enhancing user comfort and productivity during extended use. Complete Torque Control (CTC)®: A patented 2-stage clutch system maximum control in bind-up situations, preventing sudden torque reaction and increasing user safety. Electronic Variable Speed: Allows users to control drilling and chipping speeds while maintaining performance under load. Trigger Lock On: Offers increased user comfort for extended chipping applications. Rear Handle Mount: Designed to reduce bending over during down-drilling applications. Electronic Soft Start: Provides increased control when the trigger is pulled, allowing for a smoother startup. Chisel Rotation Mode: Enables users to rotate the chisel without removing it from the tool for specific demolition tasks. Mode Selector: Allows for rotation stop (for chasing and chiseling) or impact stop (for wood and metal rotary drilling). Dust Sealing Protection: Features unique dust sealing to prevent ingress into the hammer mechanism, enhancing durability and extending tool life. Magnesium Housing: Contributes to a lower tool weight and provides excellent durability. Ergonomic Design: Compact and slim line design maximizes control and offers easy access to confined spaces. Oil-Filled Gearbox: Ensures total component lubrication and superior heat dissipation for increased efficiency and durability. Included Components (D25651K model) * (1) DeWalt D25651 SDS Max Combination Hammer (1) 360° Side Handle (1) Kitbox (1) User's Guide / Product Manual Why Choose Aumictech for the DeWalt D25651? At Aumictech, we specialize in supplying high-end power tool equipment. Whether you need solid rotary hammers for demanding construction projects, reliable demolition tools for heavy-duty applications, or durable drilling solutions for concrete and masonry, our team ensures the DeWalt D25651 delivers maximum performance for your application.

D25651 Characteristics / Specifications

PARAMETER	VALUE
Model	D25651
Instrument Type	SDS Max / spline combination hammer
Motor Current	13.5 A
Impact Energy	8.0 J (9.5 ft-lb)
No Load Speed	210 to 415 rpm
Blows Per Minute	1430 to 2840 bpm
Concrete Capacity	1-3/4 in (45 mm)
Optimal Concrete Drilling	1/2 in to 1-3/8 in
Chuck Class	SDS Max and spline combination hammer family
Clutch	2 stage CTC
Vibration Control	SHOCKS active vibration control
Vibration Measurement	9.1 m/s ²
Chipping	yes
Tool Length	18.6 in
Tool Weight	15.5 lb
Power Source	corded
Operating Modes	hammerdrilling and chipping
Trigger Lock	lock on for extended chipping
Side Handle	360 degree side handle class (kit listings)
Manufacturer	DeWalt
Literature	DeWalt D25651 combination hammer listings and D25651/D25851 family manual capacity table
Family	D25602 / D25651 45 mm SDS Max spline combination hammers
Brand Lineage	DeWalt
Queue Title	Dewalt D25651

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications	
Specifications	
PARAMETER	VALUE
Model	D25651
Instrument Type	SDS Max / spline combination hammer
Motor Current	13.5 A
Impact Energy	8.0 J (9.5 ft-lb)
No Load Speed	210 to 415 rpm
Blows Per Minute	1430 to 2840 bpm
Concrete Capacity	1-3/4 in (45 mm)
Optimal Concrete Drilling	1/2 in to 1-3/8 in
Chuck Class	SDS Max and spline combination hammer family
Clutch	2 stage CTC
Vibration Control	SHOCKS active vibration control
Vibration Measurement	9.1 m/s2
Chipping	yes
Tool Length	18.6 in
Tool Weight	15.5 lb
Power Source	corded
Operating Modes	hammerdrilling and chipping
Trigger Lock	lock on for extended chipping
Side Handle	360 degree side handle class (kit listings)
Manufacturer	DeWalt
Literature	DeWalt D25651 combination hammer listings and D25651/D25851 family manual capacity table
Family	D25602 / D25651 45 mm SDS Max spline combination hammers
Brand Lineage	DeWalt
Queue Title	DeWalt D25651
Notes	
From DeWalt D25651 combination-hammer listings and D25651/D25851 family manual (45 mm SDS-Max/spline, 13.5 A,	

8.0 J, 210-415 rpm, 1430-2840 bpm). Kit box contents vary by D25651K versus bare D25651.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.