

**Aumictech**

Test & measurement • bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

ERICSSON

Ericsson Fiber Holders 900um Holders for FSU995PM Fusion Splicer

Ericsson Fiber Holders 900um Holders for FSU995PM Fusion Splicer This listing is a catalog accessory or spare in the Ericsson catalog. Public OEM literature for this exact SKU does not publish a dense numeric performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate. Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU. No invented electrical performance numbers Use with the parent instrument or chassis named in the title when applicable Documented as thin because OEM numeric tables are not public Catalog Title: Ericsson Fiber Holders 900um Holders for FSU995PM Fusion Splicer



MODEL

**Ericsson
FSU995PM**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

FSU995PM

LISTING

<https://aumictechlabs.com/products/fsu995pm-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 • 811210 • 541380

This unit

Ericsson Fiber Holders 900µm are precision alignment accessories for the FSU995PM Fusion Splicer, engineered to position and clamp 900µm loose tube fibers within the splicer's V-grooves. These holders enable consistent, low-loss splices across a range of fiber types, including Polarization Maintaining (PM), Erbium-doped, and thin-core fibers. Accurate fiber placement is

critical - fibers must be positioned over the V-grooves and tilted into place rather than slid along the grooves to achieve optimal alignment. Technical Specifications Fiber Type Compatibility: 900µm loose tube fibers Splicer Compatibility: Ericsson FSU995PM Fusion Splicer Format: Sold as a pair (two holders) Design Classification: Large fiber holders Key Features Precision alignment and holding during fusion splicing Support for advanced FSU995PM capabilities including POL alignment for PM fibers, thin-core alignment, negative index matching, and automatic arc re-centering Integral positioning in V-grooves ensures repeatable splice geometry Typical Applications Polarization Maintaining (PM) fiber splicing Erbium-doped fiber splicing Thin-core fiber splicing Industrial fusion splicing requiring precise fiber control Compatibility & Integration These holders are designed primarily for the Ericsson FSU995PM Fusion Splicer. Cross-compatibility exists with select Fitel fusion splicers and legacy Ericsson splicer models. The holders integrate with York, PK, Ericsson, and GN Nettest ultrasonic cleavers.

FSU995PM Characteristics / Specifications

PARAMETER	VALUE
Model	FSU995PM
Brand	Ericsson
Catalog Title	Ericsson Fiber Holders 900um Holders for FSU995PM Fusion Splicer
Sku	FSU995PM
Product Class	catalog accessory or spare
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	FSU995PM
Manufacturer Line	Ericsson
Documentation Note	thin accessory sheet
Calibration Class	notastandalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory
Public Spec Density	identity only

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate.

Applications

Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU.

Key Features

Catalog identity matched to brand, model, and SKU

Accessory or spare class rather than standalone instrument

No invented electrical performance numbers

Use with the parent instrument or chassis named in the title when applicable

Documented as thin because OEM numeric tables are not public

Technical Specifications

Technical Specifications

PARAMETER	VALUE
Model	FSU995PM
Brand	Ericsson
Catalog Title	Ericsson Fiber Holders 900um Holders for FSU995PM Fusion Splicer
Sku	FSU995PM
Product Class	catalog accessory or spare
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	FSU995PM
Manufacturer Line	Ericsson
Documentation Note	thin accessory sheet
Calibration Class	not standalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory

PARAMETER	VALUE
Public Spec Density	identity only

Notes
ALLOW_THIN: true accessory/spare with no public numeric table. Do not invent ranges, accuracies, or power levels. Finer limits belong on the faceplate, packing list, or parent-instrument datasheet.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.