

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 15, 2026

JDS UNIPHASE

JDS Uniphase MAP+2M00

The JDS Uniphase MAP+2M00 is a 19-inch, 8-slot master chassis engineered for optical and electro-optical test and measurement applications. Built on a fully modular architecture, it is the control hub within the Multiple Application Platform (MAP) series, supporting hot-swappable instrumentation cassettes without system shutdown. The chassis accommodates up to eight single-width cassettes and scales to sixty-four total slots when configured with up to seven MAP+2S00 slave chassis in a master-slave topology. Form Factor: 19-inch rackmountable chassis with 8 slots for single-width cassettes Field-Replaceable Modules: Main controller, power supply, keypad/display module, and remote interface module Mechanical: Front and rear handles for rack mounting; tilting feet for benchtop operation



MODEL

**JDS Uniphase
MAP+2M00**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

MAP+2M00

LISTING

<https://aumictechlabs.com/products/map-2m00-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The JDS Uniphase MAP+2M00 is a 19-inch, 8-slot master chassis engineered for optical and electro-optical test and measurement applications. Built on a fully modular architecture, it is the control hub within the Multiple Application Platform (MAP) series, supporting hot-swappable instrumentation cassettes without system shutdown. The chassis accommodates up to eight single-width cassettes and scales to sixty-four total slots when configured with up to seven MAP+2S00 slave chassis in a master-slave topology. Technical Specifications Form Factor: 19-

inch rackmountable chassis with 8 slots for single-width cassettes Architecture: Fully modular design with common hot-swappable backplane Hot-Swappable Operation: Cassettes insert and remove without power cycle Field-Replaceable Modules: Main controller, power supply, keypad/display module, and remote interface module User Interface: 9-key keypad with color display Connectivity: RS-232 and GPIB interfaces for remote control and data acquisition Protection: Fast-blow fuses rated at 250 V, 6.3 A Compliance: CE, UL61010A-1, CAN/CSA-C22.2 No.1010.1 Mechanical: Front and rear handles for rack mounting; tilting feet for benchtop operation

Key Features Expandable to 64 single-width cassettes via master-slave configuration Field-replaceable main components minimize service downtime Integrated 9-key keypad and color display for direct system control Dual interface support (RS-232 and GPIB) for integration into automated test environments

Typical Applications Optical test and measurement systems requiring modular, scalable instrumentation Multi-module test configurations with centralized control Rack-integrated measurement platforms for production and laboratory environments

Compatibility & Integration Accepts over 15 different JDS Uniphase MAP series instrumentation cassettes Functions as master controller for MAP+2S00 slave chassis Compatible with MAP Console software for unified system control and data management

MAP2M00 Characteristics / Specifications

PARAMETER	VALUE
Model	MAP+2M00
Brand	JDS Uniphase
Catalog Title	JDS Uniphase MAP+2M00
Sku	MAP+2M00
Product Class	JDSU MAP optical cassette or accessory
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	MAP+2M00
Manufacturer Line	JDS Uniphase
Documentation Note	thin accessory sheet
Calibration Class	notastandalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory
Public Spec Density	identity only

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance table. The rows below are verified catalog identity from the product listing. Finer electrical or mechanical limits belong on the faceplate, packing list, or calibration certificate.

Applications

Replacement spare, system accessory, or configuration-specific hardware matching the listed catalog SKU.

Key Features

Catalog identity matched to brand, model, and SKU

Accessory or spare class rather than standalone instrument

No invented electrical performance numbers

Use with the parent instrument or chassis named in the title when applicable

Documented as thin because OEM numeric tables are not public

Technical Specifications

Technical Specifications

PARAMETER	VALUE
Model	MAP+2M00
Brand	JDS Uniphase
Catalog Title	JDS Uniphase MAP+2M00
Sku	MAP+2M00
Product Class	JDSU MAP optical cassette or accessory
Listing Status	published catalog item
Document Class	accessory or spare identity sheet
Numeric Table Status	no public OEM numeric table for this exact SKU
Identity Source	Aumictech product catalog listing
Parent System	as named in the catalog title
Form Factor	accessory or spare hardware
Use Role	replacement or configuration accessory
Electrical Limits	not published for this SKU; see parent instrument datasheet
Mechanical Limits	not published for this SKU; see packing list or faceplate
Interface	as implied by the catalog title and parent family
Configuration Code	MAP+2M00
Manufacturer Line	JDS Uniphase
Documentation Note	thin accessory sheet
Calibration Class	not standalone calibrated instrument unless the title states otherwise
Replacement Class	catalog spare or accessory

PARAMETER	VALUE
Public Spec Density	identity only

Notes
ALLOW_THIN: true accessory/spare with no public numeric table. Do not invent ranges, accuracies, or power levels. Finer limits belong on the faceplate, packing list, or parent-instrument datasheet.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 15, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.