

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 14, 2026

AGILENT / KEYSIGHT

Keysight N6735B DC Power Module, 0 to 60 Vdc, 0 to 0.8 A, 50 W

Agilent Keysight N6735B Basic DC Power Module 60 V 0.8 A 50 W The Agilent/Keysight N6735B is a 50 W basic DC power module for N6700/N6705 mainframes rated 0 to 60 V / 0 to 0.8 A / 50 W. OEM N6700 Modular Power System Family datasheets list ripple noise programming accuracy and measurement accuracy for this model row. ATE and R&D DC rails needing 50 W at up to 60 V in a single N6700/N6705 slot. Optional output disconnect relays Option 761 The Agilent/Keysight N6735B is a 50 W basic DC power module for N6700/N6705 mainframes rated 0 to 60 V / 0 to 0.8 A / 50 W. OEM N6700 Modular Power System Family datasheets list ripple noise programming accuracy and measurement accuracy for this model row. ATE and R&D DC rails needing 50 W at up to 60 V in a single N6700/N6705 slot. Optional output disconnect relays Option 761 Compatible with N6700 and N6705 mainframes



MODEL

**Agilent / Keysight
N6735B**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

N6735B

LISTING

<https://aumictechlabs.com/products/n6735b-3/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Agilent/Keysight N6735B is a precision DC power module, part of the N6700 modular power system family. It has exceptional accuracy and resolution, making it suitable for sensitive measurements and automated testing environments. Key features include programmable voltage

and current limits, remote sensing, and comprehensive protection features to safeguard both the power supply and the device under test. The N6735B ensures stable and repeatable results, essential for efficient product development and manufacturing.

N6735B Characteristics / Specifications

PARAMETER	VALUE
Model	N6735B
DC Output Voltage	0 to 60 V
DC Output Current	0 to 0.8 A
DC Output Power	50 W
Ripple Noise Voltage Peak To Peak	25 mV
Ripple Noise Voltage RMS	9 mV
Voltage Programming Accuracy	0.1 percent + 60 mV
Current Programming Accuracy	0.15 percent + 20 mA
Voltage Measurement Accuracy	0.1 percent + 60 mV
Current Measurement Accuracy	0.15 percent + 4 mA
Mainframe Compatibility	N6700 and N6705 series
Slot Occupancy	1 of 4 slots
Arbitrary Waveform Generation	Yes
Output Disconnect Relays Option	Option 761
Polarity Reversal Relays Option	Option 760 (current limited on some models per OEM note)
Series Family	Keysight N6700 basic DC modules
Module Class	50 W basic
PARD Bandwidth	20 Hz to 20 MHz
Programming Accuracy Temperature	23 C plus or minus 5 C after 30 minute warm-up class family
Load Effect Voltage	13 mV
Load Effect Current	2 mA
Source Effect Voltage	6 mV
Source Effect Current	1 mA
Load Transient Recovery Time	less than 200 us
Measurement Data Points Default	1024

PARAMETER	VALUE
Measurement Time Interval Default	20.48 us
Current Derating Above 40 C	1 percent perCO Output Isolation: floating isolated from chassis ground class family
Bandwidth	20 Hz to 20 MHz
Output isolation	floating isolated from chassis ground class family

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

performance DC power module Occupies one mainframe slot Arbitrary waveform generation capable Optional output disconnect relays Option 761 Compatible with N6700 and N6705 mainframes	
Technical Specifications	
Technical Specifications	
PARAMETER	VALUE
Model	N6735B
DC Output Voltage	0 to 60 V
DC Output Current	0 to 0.8 A
DC Output Power	50 W
Ripple Noise Voltage Peak To Peak	25 mV
Ripple Noise Voltage RMS	9 mV
Voltage Programming Accuracy	0.1 percent + 60 mV
Current Programming Accuracy	0.15 percent + 20 mA
Voltage Measurement Accuracy	0.1 percent + 60 mV
Current Measurement Accuracy	0.15 percent + 4 mA
Mainframe Compatibility	N6700 and N6705 series
Slot Occupancy	1 of 4 slots
Arbitrary Waveform Generation	Yes
Output Disconnect Relays Option	Option 761
Polarity Reversal Relays Option	Option 760 (current limited on some models per OEM note)
Series Family	Keysight N6700 basic DC modules
Module Class	50 W basic
PARD Bandwidth	20 Hz to 20 MHz
Programming Accuracy Temperature	23 C plus or minus 5 C after 30 minute warm-up class family
Load Effect Voltage	13 mV
Load Effect Current	2 mA
Source Effect Voltage	6 mV
Source Effect Current	1 mA

PARAMETER	VALUE
Load Transient Recovery Time	less than 200 us
Measurement Data Points Default	1024
Measurement Time Interval Default	20.48 us
Current Derating Above 40 C	1 percent perCOoutput Isolation: floating isolated from chassis ground class family

Notes

From Keysight N6700 Modular Power System Family Data Sheet DC Power Module Key Performance Specifications row for N6735B. Option 760 limits output current to 10 A maximum on N6773A per OEM note.

Ordering Information

OPTION	DESCRIPTION
Option 761	Compatible with N6700 and N6705 mainframes
Option 760	limits output current to 10 A maximum on N6773A per OEM note.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 14, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.