

**Aumictech**

Test & measurement · bought, sold, repaired, calibrated

Data Sheet

August 13, 2026

YOKOGAWA

Yokogawa DLM2034 350MHz Mixed Signal Oscilloscope

The Yokogawa DLM2034 is a 350 MHz DLM2000 mixed-signal oscilloscope with 4 analog or 3 analog + 8 bit logic for embedded, power electronics, and mechatronics debug. It combines long-memory analog capture at up to 2.5 GS/s with optional logic analysis, serial-bus decode options, and power-analysis packages. Mixed analog and digital embedded system validation; power electronics switching and timing debug; serial bus trigger and decode with optional /Fxx packages; long-record intermittent fault capture; automotive and industrial control troubleshooting. Bandwidth Limit Filters: FULL plus 200 MHz down to 8 kHz (14 settings per channel) Residual Noise: 0.4 mV rms or 0.05 div rms typical History Memory: up to 20,000 waveforms standard (/M2 or /M2S up to 100,000 on DLM5000) Specs from Yokogawa DLM2000 datasheet (DLM2034). Memory lengths depend on /M1, /M2, or /M3 options and channel/interleave mode; confirm installed options on the unit.



MODEL

**Yokogawa
DLM2034**

CALIBRATION

**Available on
request**

CONDITION

Used

STATUS

In stock

RFQ / SKU

DLM2034

LISTING

<https://aumictechlabs.com/products/dlm2034-2/>

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 · 811210 · 541380

This unit

The Yokogawa DLM2034 is a versatile mixed signal oscilloscope range of applications. It has 4 analog channels and a wide bandwidth of 350 MHz. With its advanced triggering and analysis

capabilities, the DLM2034 enables engineers to capture and analyze complex signals with ease. The large display provides clear visibility of waveforms and measurement data, enhancing productivity.

Features & description

From manufacturer datasheet

Features

- 350 MHz analog bandwidth, 4 channel configuration

DLM2034 Characteristics / Specifications

PARAMETER	VALUE
Model	DLM2034
Manufacturer	Yokogawa
Instrument Type	Mixed Signal Oscilloscope
Series	DLM2000
Analog Channels	4 analog or 3 analog + 8 bit logic
Bandwidth	350 MHz
Max Sample Rate Real Time	2.5 GS/s
Max Sample Rate Interleave Off	1.25 GS/s
Max Sample Rate Repetitive	125 GS/s
A/D Resolution	8 bit (25 LSB/div); max 12 bit High Resolution mode
Logic Inputs	8 bit (switchable on CH4)
Vertical Sensitivity 1 MOhm	500 uV/div to 10 V/div (200 MHz models); scales with bandwidth
Vertical Sensitivity 50 Ohm	500 uV/div to 1 V/div
Input Coupling	AC 1 MOhm; DC 1 MOhm; DC 50 Ohm
Input Impedance	1 MOhm +/-1.0%; 50 Ohm +/-1.0%
Max Input Voltage 1 MOhm	300 Vrms or 400 Vpeak
Max Input Voltage 50 Ohm	5 Vrms or 10 Vpeak
Timebase Range	1 ns/div to 500 s/div
Timebase Accuracy	+/-2.5 ppm (shipping); +/-1.0 ppm/year ageing
Record Length Standard Repeat	6.25 M
Record Length Standard Single	25 M points
Record Length Option Max	250 M points (/M3)
Bandwidth Limit Filters	FULL plus 200 MHz down to 8 kHz (14 settings per channel)
Display	8.4-inch LCD
Ch to Ch Isolation	-34 dB typical

PARAMETER	VALUE
Residual Noise	0.4 mV rms or 0.05 div rms typical
Logic Max Sample Rate	625 MS/s
History Memory	up to 20,000 waveforms standard (/M2 or /M2S up to 100,000 on DLM5000)
Alias	DLM2034 Notes Specs from Yokogawa DLM2000 datasheet (DLM2034). Memory lengths depend on /M1, /M2, or /M3 options and channel/interleave mode; confirm installed options on the unit.
Optional serial buses	UART/I2C/SPI, CAN/CAN FD/LIN, FlexRay, SENT, CXPI, PSI5

Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications	
Specifications	
PARAMETER	VALUE
Model	DLM2034
Manufacturer	Yokogawa
Instrument Type	Mixed Signal Oscilloscope
Specifications	
PARAMETER	VALUE
Series	DLM2000
Analog Channels	4 analog or 3 analog + 8 bit logic
Bandwidth	350 MHz
Specifications	
PARAMETER	VALUE
Max Sample Rate Real Time	2.5 GS/s
Max Sample Rate Interleave Off	1.25 GS/s
Max Sample Rate Repetitive	125 GS/s
Specifications	
PARAMETER	VALUE
A/D Resolution	8 bit (25 LSB/div); max 12 bit High Resolution mode
Logic Inputs	8 bit (switchable on CH4)
Vertical Sensitivity 1 MOhm	500 uV/div to 10 V/div (200 MHz models); scales with bandwidth
Specifications	
PARAMETER	VALUE
Vertical Sensitivity 50 Ohm	500 uV/div to 1 V/div
Input Coupling	AC 1 MOhm; DC 1 MOhm; DC 50 Ohm
Input Impedance	1 MOhm +/-1.0%; 50 Ohm +/-1.0%

Specifications

PARAMETER	VALUE
Max Input Voltage 1 MOhm	300 Vrms or 400 Vpeak
Max Input Voltage 50 Ohm	5 Vrms or 10 Vpeak
Timebase Range	1 ns/div to 500 s/div

Specifications

PARAMETER	VALUE
Timebase Accuracy	+/-2.5 ppm (shipping); +/-1.0 ppm/year ageing
Record Length Standard Repeat	6.25 M
Record Length Standard Single	25 M points

Specifications

PARAMETER	VALUE
Record Length Option Max	250 M points (/M3)
Bandwidth Limit Filters	FULL plus 200 MHz down to 8 kHz (14 settings per channel)
Display	8.4-inch LCD

Specifications

PARAMETER	VALUE
Ch to Ch Isolation	-34 dB typical
Residual Noise	0.4 mV rms or 0.05 div rms typical
Logic Max Sample Rate	625 MS/s

History Memory: up to 20,000 waveforms standard (/M2 or /M2S up to 100,000 on DLM5000)

Alias: DLM2034

Notes

Specs from Yokogawa DLM2000 datasheet (DLM2034). Memory lengths depend on /M1, /M2, or /M3 options and channel/interleave mode; confirm installed options on the unit.

Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: Available on request. Used · In stock.

Request a quote: sales@aumictech.com · +1 (484) 841-9341

Aumictech

788 S 500 E, Pleasant Grove, UT 84062
sales@aumictech.com · +1 (484) 841-9341
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·
30-day returns
NAICS 423690 · 811210 · 541380
Generated August 13, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.