

**Aumictech**

Test &amp; measurement • bought, sold, repaired, calibrated

**Data Sheet**

August 3, 2026

YOKOGAWA

# Yokogawa MV1006 Portable Paperless Recorder, 6 Ch, 1 S (Fast sampling mode: 125 ms)

Yokogawa MV1006 Portable Paperless Recorder, 6 Ch, 1 S (Fast sampling mode: 125 ms) The MV1006 provides a portable MVAdvanced / MV1000-family paperless recorder with 6 universal input channels, 1 s normal sampling, and 125 ms fast sampling mode for multi-channel laboratory, plant, and test-stand data logging. Six-channel temperature, voltage, and process signal recording; portable paperless logging with network access; CompactFlash/USB archival; stand-alone bench and field evaluation data capture. The MV1006 provides a portable MVAdvanced / MV1000-family paperless recorder with 6 universal input channels, 1 s normal sampling, and 125 ms fast sampling mode for multi-channel laboratory, plant, and test-stand data logging. Six-channel temperature, voltage, and process signal recording; portable paperless logging with network access; CompactFlash/USB archival; stand-alone bench and field evaluation data capture.

No photo

MODEL

**Yokogawa MV1006**

CALIBRATION

**N/A — off-catalog  
OEM datasheet**

CONDITION

**See OEM  
documentation**

STATUS

**Not listed on  
Aumictech  
inventory**

RFQ / SKU

**MV1006**

LISTING

**Off-catalog — OEM dat  
asheet only**

NIST-traceable cal

SAM registered

30-day returns

NAICS 423690 • 811210 • 541380

## Features & description

---

From manufacturer datasheet

### Features

- Portable paperless recorder (MV1000 / MVAdvanced family) • 6 input channels • Sampling: 1 s normal; 125 ms fast sampling mode • Wide input types: thermocouple, RTD, DC voltage ( $\pm 50$  V class), contact • Channel-to-channel isolation; 1000 VAC withstand class • Internal memory approximately 200 MB class • CompactFlash and USB removable storage • Network: email, FTP, DHCP class functions

## MV1006 Characteristics / Specifications

| PARAMETER                | VALUE                                                                                                                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                    | MV1006                                                                                                                                                                                                                          |
| Manufacturer             | Yokogawa                                                                                                                                                                                                                        |
| Instrument Type          | Portable Paperless Recorder / Data Logger                                                                                                                                                                                       |
| Family                   | MV1000 / MVAdvanced                                                                                                                                                                                                             |
| Input Channels           | 6                                                                                                                                                                                                                               |
| Normal Sampling Interval | 1 s                                                                                                                                                                                                                             |
| Fast Sampling Mode       | 125 ms                                                                                                                                                                                                                          |
| Isolation                | Insulated between channels; 1000 VAC withstand class                                                                                                                                                                            |
| External Media           | CompactFlash; USB                                                                                                                                                                                                               |
| Related Models           | MV1008; MV1012; MV1024; MV2048                                                                                                                                                                                                  |
| Alias                    | MV1006 Standard Operating Conditions Configure channel types and ranges before acquisition. Select normal 1 s or fast 125 ms mode per signal bandwidth. Provide adequate removable media for long recordings. Operational Notes |
| Sampling                 | 1 s normal; 125 ms fast sampling mode                                                                                                                                                                                           |
| Wide input types         | thermocouple, RTD, DC voltage ( $\pm 50$ V class), contact                                                                                                                                                                      |
| Network                  | email, FTP, DHCP class functions                                                                                                                                                                                                |

# MV1006 Specifications

| PARAMETER                | VALUE                                                                                                                        |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Key Features             | - Portable paperless recorder (MV1000 / MVAdvanced family)                                                                   |
| Technical Specifications | Model: MV1006                                                                                                                |
| Operational Notes        | MV1006 is the 6-channel MV1000 portable configuration—distinct from higher channel-count MV100x/MV20xx models. Alias MV1006. |

# Full OEM specifications

Complete technical content extracted from the manufacturer datasheet. Sparse OEM tables are reconstructed as tables below; other text is preserved as paragraphs.

Specifications

Specifications

| PARAMETER                | VALUE                                                |
|--------------------------|------------------------------------------------------|
| Model                    | MV1006                                               |
| Manufacturer             | Yokogawa                                             |
| Instrument Type          | Portable Paperless Recorder / Data Logger            |
| Family                   | MV1000 / MVAdvanced                                  |
| Input Channels           | 6                                                    |
| Normal Sampling Interval | 1 s                                                  |
| Fast Sampling Mode       | 125 ms                                               |
| Isolation                | Insulated between channels; 1000 VAC withstand class |
| External Media           | CompactFlash; USB                                    |
| Related Models           | MV1008; MV1012; MV1024; MV2048                       |
| Alias                    | MV1006                                               |

Standard Operating Conditions

Configure channel types and ranges before acquisition. Select normal 1 s or fast 125 ms mode per signal bandwidth. Provide adequate removable media for long recordings.

Operational Notes

MV1006 is the 6-channel MV1000 portable configuration-distinct from higher channel-count MV100x/MV20xx models. Alias MV1006.

### Available from Aumictech

Used and refurbished unit evaluated in-house. Calibration: N/A — off-catalog OEM datasheet. See OEM documentation · Not listed on Aumictech inventory.

Request a quote: [sales@aumictech.com](mailto:sales@aumictech.com) · +1 (484) 841-9341

#### Aumictech

788 S 500 E, Pleasant Grove, UT 84062  
[sales@aumictech.com](mailto:sales@aumictech.com) · +1 (484) 841-9341  
<https://aumictechlabs.com>

NIST-traceable calibration · SAM registered ·  
30-day returns  
NAICS 423690 · 811210 · 541380  
Generated August 3, 2026

Technical content from manufacturer specifications. Unit photo/stock from Aumictech listing when available. Specifications subject to OEM documentation and unit condition.